

# PRIMUS Car Audio Speakers

**Infinity Primus Car Audio Speakers** 





PRIMUS 503F



PRIMUS 683F



PRIMUS 503CF



PRIMUS 693C



PRIMUS 603F



PRIMUS 693M



PRIMUS 603CF



PRIMUS 753T

## Refresh your car with Infinity science-inspired design speakers.

If you are looking to upgrade your driving experience with amazing audio, Infinity Primus has you covered with their patented Plus One<sup>TM</sup> woofer cone and edge-driven dome technology. Infinity's sound signature brings you lifelike vocals, crisp cymbals, and well-defined bass. Plus, their rich all-black color scheme seamlessly integrates into the car interior. Their radial starburst pattern is inspired by the icon of a supernova, punctuated with the mirror-like copper mobius strip logo. There are 8 models for the family and all features a compact design for easy installation in any vehicle. Primus delivers great Infinity sound at a price that's hard to beat.

## Features

- ► Plus One<sup>™</sup> Woofer Cone Architecture
- ► Edge-driven Silk Dome Tweeter
- Engineered to Fitment and Easy Installation
- ► Vented Basket Frame Design for Cooling
- Competitively Tuned



## PRIMUS Car Audio Speakers

**Infinity Primus Car Audio Speakers** 

## **Features and Benefits**

## Plus One™ Woofer Cone Architecture

Harman's patented (US patent #7,548,631) Plus One™ cones provide more overall speaker cone area (up to 35%) than other cones in its class

 the result is higher sensitivity (increase up to 2dB), increased low-frequency output and greater musical character.

## **Edge-driven Silk Dome Tweeter**

Infinity Primus speakers are engineered with edge-driven silk dome tweeters which expand the high-frequency range and ensure you'll hear all the natural detail of your favorite tunes.

Engineered to Fitment and Easy Installation

Infinity Primus speakers feature a compact design for easy installation in tight spaces, allowing them to fit into more vehicles without the need for modifications and cutting.

## **Vented Basket Frame Design for Cooling**

The super-rigid vented baskets help to cool the voice coils making for a reliable speaker. Not only do these look cool but they provide a real world benefit by wicking heat way from the motor structure almost like a fan as the cone moves through its stroke. The benefits are lower distortion at high output levels, a longer lasting speaker and higher power handling.

#### **Competitively Tuned**

Infinity Primus speakers are carefully tuned to ensure each line has the consistent Infinity sound signature.

## What's in the box:

#### Primus 503F

- 2x Speakers
- 8x Screws
- 8x Speed clips
- 2x 18AWG, 200mm length pigtail cable
- 1x Foam gaskets
- 2x Brand stickers
- 1x Owner's manual

## Primus 503CF

- 2x Speakers
- 2x Tweeters
- 2x In-line crossovers
- 8x Screws for speakers
- 6x Screws for tweeter kits
- 8x Speed clips
- 2x Threaded flush-mount adapters
- 2x Plastics locking nuts
- 2x Surface-mount cups
- 2x Starfish tweeter mounts
- 2x Foam gaskets
- 2x Brand stickers
- 1x Owner's manual

#### Primus 603F

- 2x Speakers
- 8x Screws
- 8x Speed clips
- 2x 18AWG, 200mm length pigtail cable
- 1x Foam gaskets
- 2x Brand stickers
- 1x Owner's manual

## Primus 603CF

- 2x Speakers
- 2x Tweeters
- 2x In-line crossovers
- 8x Screws for speakers
- 6x Screws for tweeter kits
- 8x Speed clips
- 2x Threaded flush-mount adapters
- 2x Plastics locking nuts
- 2x Surface-mount cups
- 2x Starfish tweeter mounts
- 2x Foam gaskets
- 2x Brand stickers
- 1x Owner's manual

#### Primus 683F

- 2x Speakers
- 8x Screws
- 8x Speed clips
- 2x 18AWG, 200mm length pigtail cable
- 1x Foam gaskets
- 2x Brand stickers
- 1x Owner's manual

#### Primus 693C

- 2x Speakers
- 2x Tweeters
- 2x In-line crossovers
- 2x Grilles
- 8x Screws for speakers
- 6x Screws for tweeter kits
- 8x Speed clips
- 2x Threaded flush-mount adapters
- 2x Plastics locking nuts
- 2x Surface-mount cups
- 2x Starfish tweeter mounts
- 2x Foam gaskets
- 2x Brand stickers
- 1x Owner's manual

#### Primus 693M

- 2x Speakers
- 2x Grilles
- 8x Screws
- 8x Speed clips
- 2x 18AWG, 200mm length pigtail cable
- 1x Foam gaskets
- 2x Brand stickers
- 1x Owner's manual

## Primus 753T

- 2x Tweeters
- 2x In-line crossovers
- 6x Screws
- 2x Threaded flush-mount adapters
- 2x Plastics locking nuts
- 2x Surface-mount cups
- 2x Starfish tweeter mounts
- 2x Brand stickers
- 1x Owner's manual



## PRIMUS Car Audio Speakers

Infinity Primus Car Audio Speakers



#### **Technical Specifications**

#### Primus 503F

Woofer: 5-1/4" Polypropylene Driver

Tweeter: 1/2" Silk Dome

Power Handling: 40Wrms, 120W peak

Sensitivity (2.83V@1m): 91dB

Frequency Response (-6dB): 75Hz – 20kHz

Nominal Impedance: 3.0 ohms Crossover Point: 6kHz@6dB/octave

#### Primus 503CF

Woofer: 5-1/4" Polypropylene Driver

Tweeter: 3/4" Silk Dome

Power Handling: 50Wrms, 150W peak

Sensitivity (2.83V@1m): 91dB

Frequency Response (-6dB): 75Hz - 20kHz

Nominal Impedance: 3.0 ohms
Crossover Point: 5kHz@12dB/octave

#### Primus 603F

Woofer: 6-1/2" Polypropylene Driver

Tweeter: 1/2" Silk Dome

Power Handling: 50Wrms, 150W peak

Sensitivity (2.83V@1m): 92dB

Frequency Response (-6dB): 55Hz - 20kHz

Nominal Impedance: 3.0 ohms Crossover Point: 5kHz@6dB/octave

#### Primus 603CF

Woofer: 6.5" Polypropylene Driver

Tweeter: 3/4" Silk Dome

Power Handling: 60Wrms, 180W peak

Sensitivity (2.83V@1m): 92dB

Frequency Response (-6dB): 55Hz – 20kHz

Nominal Impedance: 3.0 ohms Crossover Point: 5kHz@12dB/octave

#### Primus 683F

Woofer: 6"x8" Polypropylene Driver

Tweeter: 1/2" Silk Dome

Power Handling: 50Wrms, 150W peak

Sensitivity (2.83V@1m): 92dB

Frequency Response (-6dB): 65Hz - 20kHz

Nominal Impedance: 3.0 ohms Crossover Point: 5kHz@6dB/octave

## Primus 693C

Woofer: 6"x9" Polypropylene Driver

Tweeter: 3/4" Silk Dome

Power Handling: 80Wrms, 240W peak

Sensitivity (2.83V@1m): 93dB

Frequency Response (-6dB): 50Hz – 20kHz

Nominal Impedance: 3.0 ohms Crossover Point: 5kHz@12dB/octave

#### Primus 693M

Woofer: 6"x9" Polypropylene Driver

Tweeter: 3/4" Silk Dome

Power Handling: 60Wrms, 180W peak

Sensitivity (2.83V@1m): 93dB

Frequency Response (-6dB): 50Hz – 20kHz

Nominal Impedance: 3.0 ohms Crossover Point: 5kHz@6dB/octave

#### Primus 753T

Tweeter: 3/4" Silk Dome

Power Handling: 40Wrms, 120W peak

Sensitivity (2.83V@1m): 91dB

Frequency Response (-6dB): 2kHz – 20kHz

Nominal Impedance: 3.0 ohms Crossover Point: 5kHz@12dB/octave

